

SMART FOCUS

SENSOR TO OPEN OR MAKE
ALL TYPES OF AUTOMATIC
DOOR SAFE

Commercial sheet



WHEN ACCURACY IS IMPORTANT...

DESCRIPTION

The **SMART FOCUS** is an active infrared sensor operating with background suppression (triangulation). The **SMART FOCUS** sends a narrow infrared beam (35 x 70 mm at a height of 2,20 m).

The **SMART FOCUS** is suitable for all applications where accurate and narrow detection fields are required. It either opens, protects or monitors.


IN PRACTICE

- The **SMART FOCUS** provides safety in the following applications:
 - Sliding door during the opening cycle (risk of crushing).
 - Curved sliding or swing door during the closing cycle (risk of pinching or crushing).
 - It safeguards the potential impact point or "pinch zone" of revolving doors.
- The **SMART FOCUS**, as an alternative to pushbuttons, opens an automatic door when:
 - You need a very small detection field (restaurant kitchens, internal train doors, etc).
- A single **SMART FOCUS** or several in unison will provide safety in revolving air locks.
- The **SMART FOCUS** works vertically (with background) as well as horizontally (if necessary, without background).


RELIABILITY

- The main feature of the **SMART FOCUS** is its ability to track changes in its background and environment.
- The **SMART FOCUS**'s ability to adapt itself to variations in the background and ambient temperature ensures a greater reliability in all situations.


PERFECT FOR ALL DOORS!




Revolving doors
Safety at the pinching zone




Curved sliding doors Safety during the closing cycle




Sliding doors Safety during the opening cycle



Swinging doors Safety during the closing cycle



Restaurant door



35 × 70 mm (h=2,2 m)

INSTALLATION & ADJUSTMENT

- **PUSH & GO:** for the most common applications and installation heights, a single press on the control button is enough. The sensing area is adjusted automatically.
- **MANUAL MODE:** for special applications (greater height, reflective floors, horizontal applications, etc.), a "manual mode" using an adjusting screw and dip-switch enables precise adjustments of the sensing area.

ACCESSORIES



Spotfinder

Kit SMART FOCUS SMA
[for surface mounting]

Kit SMART FOCUS BA
[for mounting bracket]

TECHNICAL SPECIFICATIONS

Technology	Active infrared
Detection mode	Presence detection by distance measurement
Detection field	35 mm × 70 mm (at 2,2 m mounting height)
Tilt angle	-4° to +4°
Response time	32 ms - 64 ms (depending on detection speed setting)
Installation height	1,6 m - 3 m (automatic mode) 0,6 m - 3 m (manual mode)
Power supply	12 V - 24 V AC/DC -5% / +10%
Network frequency	50 - 60 Hz
Max. consumption	120 mA @ 24 V AC / 80 mA @ 24 V DC
Standard output	Relay (free of potential contact)
Max. voltage on the contacts	42 V AC/DC
Max. current on the contacts	1 A (resistive)
Max. breaking capacity	30 W (DC) / 60 VA (AC)
Monitoring input	1 optocoupler (free of potential)
Max. contact voltage	30V
Voltage threshold	High state > 10 V; low state < 1 V
Holdtime output	0,5 s
Reflective power	Min. 10% long wave infrared of 850 nm
Temperature range	-25°C / +55°C; 0-95% relative humidity
Degree of protection	IP53
Dimensions	
With bracket	144 mm (L) × 52 mm (H) × 43 mm (D)
Without bracket	110 mm (L) × 50 mm (H) × 30 mm (D)
Material of the section	ABS (black)
Length of the main cable	2,5 m
Conformity with standards	Electromagnetic compatibility (EMC) according to 2004/108/EEC

Specifications are subject to change without prior notice.

DISCLAIMER This document as well as all other enclosed documents (quotation / specification / other) are provided «as is» without warranties of any kind, either expressed or implied, including but not limited to the implied warranties of merchantability, fitness for a particular purpose, or non-infringement. / Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. / BEA has the right without liability to change descriptions and specifications at any time. / Prices, shipping and availability are subject to change without prior notice.

